LANDBOSS

1100D

LANDBOSS 1100D TICKS ALL THE BOXES FOR AUSSIE FAMERS



MODEL SPECIFICATIONS

	LANDBOSS 1100D	LANDBOSS TOOD
Engine type	24.8hp, in-line three-cylinder Kubota diesel engine	33 1100
Engine model	Kubota D1105-E3B	
Cooling	Liquid cooled	DIE
Bore x stroke	78mm x 78.4mm	
Compression ratio	24:1	
Maximum torque	72Nm @ 3000rpm	
Starter system	Electric start	
Battery/AMP hour	12V / 45Ah	
Lubrication System	Force-fed lubrication	
Transmission	CVTech high / low / neutral / reverse	
4WD	Push button 2WD / 4WD	
Differential Lock	Push button front and rear differential loc	Co
Engine Braking	Downhill descent control	
Clutch	Constant variable transmission (CVT)	
Final drive	Shaft drive	manu Taraka Salah
Front brakes	Hydraulic disc brakes	
Rear brakes	Hydraulic disc brakes	
Parking brake	Hand brake	
Steering	Electronic power steering (EPS)	1550
Drive	Right-hand drive for Aussies	
Front suspension	Independent dual A-Arm with coil-over shocks	E C
Rear suspension	Independent dual A-Arm with coil-over shocks	
Tyres (front/rear)	26x9x14 / 26x11x14	
Wheels (front/rear)	14×9 / 14×11	
Wheels	Steel five-stud	
Dimensions (L/W/H)	3018mm / 1520mm / 1905mm	
Wheelbase	1930mm	W W
Distance between wheels	990mm	OIES
Ground clearance	240mm	
Dry weight	700kg	
Fuel capacity	35 litres	
Cargo tray capacity	500kg	
Rear tray (L/W/H)	1020mm / 1470mm / 400mm	
Towing capacity	800kg	
Warranty	Two-year parts and labour	- Carolin





